

[illegible]

TIERRA

Variable

15

170 KG c./m³

CAN FF d. CC. 0150

8 a 25

292.5 Kg c./m³

25

35

170 kg. c./m³

60 (mínimo)

CORTE

Horizontal dimensions (top): 50, 50, 300, 100, 550, 550.

Vertical dimensions (left): 30, 100, 400, 120.

Horizontal dimensions (bottom): 150, 150, 400, 100, 500, 150, 150.

Material specifications:

- Hormigón 226 Kg./cm³
- Horm. 297.5 Kg./cm³
- 30 X 30 X 3 mm
- 25 X 3 mm a 25 cm
- 25 X 25 X 3 mm
- 2 L 30 X 30 X 3 mm

Other details:

- Variable
- 200
- 80
- 450
- Ø 10 a Ø 12

PLANTA

25x3mm a 25cm
30 X 30X 3 mm

200
50
50 REBAJE
300
400
50
50
50
50
100

100 50 1000 150

600
700

Technical drawing of a cross-section of a concrete slab (CORTE). The drawing includes a top view and a side view.

Top View Dimensions:

- Overall width: 150 + 300 + 150 = 600
- Overall height: 100 + 100 = 200
- Internal dimensions: 100, 150, 600, 150, 100

Side View Dimensions:

- Overall height: 30
- Overall width: 100

Reinforcement Details:

- 30x30x3 mm
- 25x3 mm
- 25x25x3 mm

Legend:

- Variable (indicated by a diagonal line through the top view)
- CORTE (indicated by a diagonal line through the side view)

Technical drawing of a staircase section showing structural details and dimensions. The drawing includes the following elements:

- Dimensions:**
 - Horizontal dimensions: 100, 700, 100.
 - Vertical dimensions: 200, 50, 50, 300, 50, 50, 200.
 - Staircase width: 700.
- Structural Details:**
 - Reinforcement bars: 25X3 mm a 2,5cm.
 - Staircase structure: 25X25X3 mm.
 - Support/Connection: 30X30X3 mm.

APROBACION